

<b>Model</b>	<b>DOE Heating Capacity</b>	<b>Net I=B=R Steam MBH</b>	<b>Net I=B=R Steam Sq. Ft.</b>	<b>I=B=R Firing Rate</b>	<b>AFUE %</b>	<b>Minimum Chimney Requirements</b>	<b>Tankless Heater GPM</b>	<b>Jacket Depth 'A'</b>	<b>Jacket Rear to Center of Flue 'B'</b>	<b>Flue Collar Diameter 'C'</b>	<b>Approx. Shipping Weight</b>
<b>CL3-091</b>	78	56	233	0.65	84.1	8" x 8" x15'	2.25	17-3/8"	8-1/4"	6"	570 lbs.
<b>CL3-105</b>	90	68	283	0.75	83.8	8" x 8" x15'	2.25	17-3/8"	8-1/4"	6"	570 lbs.
<b>CL3-140</b>	119	89	370	1.00	82.7	8" x 8" x15'	2.50	17-3/8"	8-1/4"	6"	570 lbs.
<b>CL4-126</b>	108	81	338	0.90	84.1	8" x 8" x15'	2.50	22-3/8"	10-7/8"	7"	690 lbs.
<b>CL4-175</b>	149	112	467	1.25	83.5	8" x 8" x15'	2.75	22-3/8"	10-7/8"	7"	690 lbs.
<b>CL4-210</b>	177	133	554	1.50	82.6	8" x 8" x15'	3.00	22-3/8"	10-7/8"	7"	690 lbs.
<b>CL5-168</b>	144	108	450	1.20	83.7	8" x 8" x15'	2.75	27-3/8"	13-3/8"	8"	810 lbs.
<b>CL5-245</b>	207	155	646	1.75	82.5	8" x 8" x15'	3.25	27-3/8"	13-3/8"	8"	810 lbs.
<b>CL5-280</b>	235	176	733	2.00	82.3	8" x 8" x15'	3.50	27-3/8"	13-3/8"	8"	810 lbs.

